

Safety Data Sheet

according to UK REACH Regulation

DEKASEAL 1512

Revision date: 19.05.2021

Product code: 1512

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

DEKASEAL 1512

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Adhesives, sealants

Uses advised against

No further relevant information available.

1.3. Details of the supplier of the safety data sheet

Company name: DINOL GmbH

Street: Pyrmonter Strasse 76

Place: D-32676 Luegde

Telephone: + 49 (0) 5281 982980

Telefax: + 49 (0) 5281 9829860

e-mail: msds@dinol.com

Contact person: Labor

Responsible Department: msds@dinol.com

1.4. Emergency telephone

Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)

number:**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GB CLP Regulation**

Hazard categories:

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Harmful to aquatic life with long lasting effects.

2.2. Label elements**GB CLP Regulation****Hazard statements**

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P273 Avoid release to the environment.

P312 Call a POISON CENTER/doctor if you feel unwell.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

2.3. Other hazards

Hydrocarbons: This substance does not meet the criteria for classification as CMR category 1A or 1B according to CLP. (<1 % Benzene)

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

Safety Data Sheet

according to UK REACH Regulation

DEKASEAL 1512

Revision date: 19.05.2021

Product code: 1512

Page 2 of 11

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
64742-49-0	Kohlenwasserstoffe, C9-C10, n-Alkane, Isoalkane, Cyclics, <2% Aromaten			15 - < 20 %
	927-241-2		01-2119471843-32	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 3; H226 H336 H304 H412 EUH066			
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics			1 - < 5 %
	919-857-5	649-327-00-6	01-2119463258-33	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1; H226 H336 H304 EUH066			
128-37-0	2,6-Di-tert-butyl-p-kresol			< 1 %
	204-881-4			
	Aquatic Acute 1, Aquatic Chronic 1; H400 H410			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
64742-49-0	927-241-2	Kohlenwasserstoffe, C9-C10, n-Alkane, Isoalkane, Cyclics, <2% Aromaten	15 - < 20 %
		inhalation: LC50 = >5000 mg/l (vapours); dermal: LD50 = >5000 mg/kg; oral: LD50 = >5000 mg/kg	
	919-857-5	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	1 - < 5 %
		inhalation: LC50 = >5000 mg/l (vapours); dermal: LD50 = >5000 mg/kg; oral: LD50 = >5000 mg/kg	
128-37-0	204-881-4	2,6-Di-tert-butyl-p-kresol	< 1 %
		dermal: LD50 = >5000 mg/kg; oral: LD50 = >5000 mg/kg	

Further Information

Hydrocarbons meet the requirements for not being classified as carcinogenic (<0,1% benzene alt<3% (w/w) DMSO extract (IP 346)).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice.
Never give anything by mouth to an unconscious person or a person with cramps.
If unconscious place in recovery position and seek medical advice.

After inhalation

Remove casualty to fresh air and keep warm and at rest.

After contact with skin

Change contaminated clothing.
After contact with skin, wash immediately with plenty of water and soap.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).
Do NOT induce vomiting.
Call a physician immediately.
Put victim at rest, cover with a blanket and keep warm.

Safety Data Sheet

according to UK REACH Regulation

DEKASEAL 1512

Revision date: 19.05.2021

Product code: 1512

Page 3 of 11

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**alcohol resistant foam, Carbon dioxide (CO₂), Extinguishing powder. Water fog.**Unsuitable extinguishing media**

High power water jet.

5.2. Special hazards arising from the substance or mixture

No further relevant information available.

5.3. Advice for firefighters

Use suitable breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General measures**

Avoid contact with skin, eyes and clothes. Use personal protection equipment.

For emergency responders

For further specification, refer to section 8 of the SDS.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up**For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

Other information

No information available.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Use only outdoors or in a well-ventilated area.

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Usual measures for fire prevention.

Safety Data Sheet

according to UK REACH Regulation

DEKASEAL 1512

Revision date: 19.05.2021

Product code: 1512

Page 4 of 11

Advice on general occupational hygiene

The usual precautionary measures are to be adhered to when handling chemicals.
Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately.
Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

No special measures are necessary.

Hints on joint storage

Not required.

7.3. Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
128-37-0	2,6-Di-tert-butyl-p-cresol	-	10		TWA (8 h)	WEL
7727-43-7	Barium sulphate, inhalable dust	-	10		TWA (8 h)	WEL

Safety Data Sheet

according to UK REACH Regulation

DEKASEAL 1512

Revision date: 19.05.2021

Product code: 1512

Page 5 of 11

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
7727-43-7	Bariumsulfat			
Worker DNEL, long-term		inhalation	systemic	10 mg/m³
Worker DNEL, long-term		inhalation	local	10 mg/m³
Consumer DNEL, long-term		inhalation	systemic	10 mg/m³
Consumer DNEL, long-term		oral	systemic	13000 mg/kg bw/day
64742-49-0	Kohlenwasserstoffe, C9-C10, n-Alkane, Isoalkane, Cyclics, <2% Aromaten			
Worker DNEL, long-term		inhalation	systemic	871 mg/m³
Worker DNEL, long-term		dermal	systemic	77 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	185 mg/m³
Consumer DNEL, long-term		dermal	systemic	46 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	46 mg/kg bw/day
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics			
Worker DNEL, long-term		dermal	systemic	208 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	871 mg/m³
Consumer DNEL, long-term		inhalation	systemic	185 mg/m³
Consumer DNEL, long-term		dermal	systemic	125 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	125 mg/kg bw/day
,				
128-37-0	2,6-Di-tert-butyl-p-kresol			
Worker DNEL, long-term		inhalation	systemic	3,5 mg/m³
Worker DNEL, acute		inhalation	systemic	18 mg/m³
Worker DNEL, long-term		dermal	systemic	0,5 mg/kg bw/day
Worker DNEL, acute		dermal	systemic	19 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0,78 mg/m³
Consumer DNEL, acute		inhalation	systemic	3,1 mg/m³
Consumer DNEL, long-term		dermal	systemic	0,25 mg/kg bw/day
Consumer DNEL, acute		dermal	systemic	6,7 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,25 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	1 mg/kg bw/day

Safety Data Sheet

according to UK REACH Regulation

DEKASEAL 1512

Revision date: 19.05.2021

Product code: 1512

Page 6 of 11

PNEC values

CAS No	Substance	
Environmental compartment		Value
7727-43-7	Bariumsulfat	
Freshwater		0,115 mg/l
Freshwater sediment		600,4 mg/kg
Micro-organisms in sewage treatment plants (STP)		62,2 mg/l
Soil		207,7 mg/kg
128-37-0	2,6-Di-tert-butyl-p-kresol	
Freshwater		0,000199-0,0023 mg/l
Marine water		0,0000199-0,00023 mg/l
Freshwater sediment		0,0996-3,4 mg/kg
Marine sediment		0,00996-0,34 mg/kg
Micro-organisms in sewage treatment plants (STP)		0,17-100 mg/kg

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Individual protection measures, such as personal protective equipment

Eye/face protection

Recommended eye protection articles :

Eye glasses with side protection (DIN EN 166)

Hand protection

Recommended glove articles :

FKM (fluoro rubber), Breakthrough time (maximum wearing time): 480 min.

NBR (Nitrile rubber), Breakthrough time (maximum wearing time): 480 min.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.

Protect skin by using skin protective cream.

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

Work in well-ventilated zones or use proper respiratory protection.

gas filtering equipment (EN 141). Filter material/medium :A

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:

Paste

Safety Data Sheet

according to UK REACH Regulation

DEKASEAL 1512

Revision date: 19.05.2021

Product code: 1512

Page 7 of 11

Colour: whitish
 Odour: characteristic
 Odour threshold: not determined

Test method

Changes in the physical state

Melting point/freezing point: not determined
 Boiling point or initial boiling point and boiling range: 136-164 °C
 Flash point: > 70 °C

Flammability

Solid/liquid: not determined
 Gas: not determined

Explosive properties

not determined

Lower explosion limits: 0,6 vol. %
 Upper explosion limits: 7 vol. %
 Auto-ignition temperature: > 200 °C
 Decomposition temperature: not determined

Oxidizing properties

not determined

pH-Value: not applicable

Viscosity / dynamic: (at 20 °C) 2.500 mPa·s

Viscosity / kinematic: not applicable

Water solubility: The study does not need to be conducted because the substance is known to be insoluble in water.

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined

Vapour pressure: (at 20 °C) 5 hPa

Vapour pressure: (at 50 °C) 30 hPa

Density (at 20 °C): 1,5 g/cm³ DIN 51757

9.2. Other information

Other safety characteristics

Solvent content: 17,3 %
 Solid content: 80,7 %

Further Information

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

DEKASEAL 1512

Revision date: 19.05.2021

Product code: 1512

Page 8 of 11

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

No further relevant information available.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Carbon monoxide

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-49-0	Kohlenwasserstoffe, C9-C10, n-Alkane, Isoalkane, Cyclics, <2% Aromaten				
	oral	LD50 >5000 mg/kg	Rat		
	dermal	LD50 >5000 mg/kg	Rabbit		
	inhalation vapour	LC50 >5000 mg/l	Rat		
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics				
	oral	LD50 >5000 mg/kg	Rat		
	dermal	LD50 >5000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 >5000 mg/l	Rat		
128-37-0	2,6-Di-tert-butyl-p-kresol				
	oral	LD50 >5000 mg/kg	Rat		
	dermal	LD50 >5000 mg/kg	Rat		

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to UK REACH Regulation

DEKASEAL 1512

Revision date: 19.05.2021

Product code: 1512

Page 9 of 11

Further information

There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

There are no data available on the mixture itself.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
128-37-0	2,6-Di-tert-butyl-p-kresol					
	Acute crustacea toxicity	EC50 0,48-0,61 mg/l	48 h			

12.2. Persistence and degradability

There are no data available on the mixture itself.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
64742-49-0	Kohlenwasserstoffe, C9-C10, n-Alkane, Isoalkane, Cyclics, <2% Aromaten			
	OECD 301F	> 60 %	28	
	Leicht biologisch abbaubar (nach OECD-Kriterien).			
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics			
	OECD 301F	> 60 %	28	
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
128-37-0	2,6-Di-tert-butyl-p-kresol	5,10

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

not applicable

12.7. Other adverse effects

No information available.

Further information

There are no data available on the mixture itself.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation.

Do not mix with other wastes.

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Safety Data Sheet

according to UK REACH Regulation

DEKASEAL 1512

Revision date: 19.05.2021

Product code: 1512

Page 10 of 11

Contaminated packaging

Dispose according to legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.
Marine pollutant:	no

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Maritime transport in bulk according to IMO instruments

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3

2004/42/EC (VOC): 17,33 %
260,0 g/l

Information according to 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

Additional information

Observe in addition any national regulations!

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

National regulatory information

Safety Data Sheet

according to UK REACH Regulation

DEKASEAL 1512

Revision date: 19.05.2021

Product code: 1512

Page 11 of 11

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

Additional information

Das Gemisch enthält die folgenden besonders besorgniserregenden Stoffe (SVHC), die in der Kandidatenliste gemäß REACH, Artikel 59 enthalten sind: keine/keiner

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H336 May cause drowsiness or dizziness.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)