

according to Regulation (EC) No 1907/2006

DEKASEAL 8936 BLACK

Revision date: 04.03.2021 Product code: 1145 Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

DEKASEAL 8936 BLACK

UFI: 2A53-Q044-G000-78TV

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Adhesives, sealants

Uses advised against

No further relevant information available.

1.3. Details of the supplier of the safety data sheet

Company name: DINOL GmbH

Street: Pyrmonter Strasse 76
Place: D-32676 Luegde

Telephone: + 49 (0) 5281 982980 Telefax: + 49 (0) 5281 9829860

e-mail: msds@dinol.com

Contact person: Labor

Responsible Department: msds@dinol.com

1.4. Emergency telephone Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Skin corrosion/irritation: Skin Irrit. 2

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements: Causes skin irritation.

Harmful to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Signal word: Warning

Pictograms:



Hazard statements

H315 Causes skin irritation.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P264 Wash water thoroughly after handling.
P273 Avoid release to the environment.

P280 Wear protective gloves and eye/face protection.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.

2.3. Other hazards

No information available.



according to Regulation (EC) No 1907/2006

DEKASEAL 8936 BLACK

Revision date: 04.03.2021 Product code: 1145 Page 2 of 11

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name				
	EC No	Index No	REACH No		
	GHS Classification				
	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics				
	927-510-4	649-328-00-1	01-2119475515-33		
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411				
	Hydrocarbons, C6, isoalkanes, <5% n-hexane				
	931-254-9	649-328-00-1	01-2119484651-34		
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411				

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
	927-510-4	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	5 - < 10 %
	inhalation: LC50 = >193 mg/l (vapours); dermal: LD50 = >2600 mg/kg; oral: LD50 = > 5000 mg/kg		

Further Information

Hydrocarbons meet the requirements for not being classified as carcinogenic (<0,1% benzene alt<3% (w/w) DMSO extract (IP 346)).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Change contaminated clothing.

After inhalation

If unconscious place in recovery position and seek medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap.

In case of skin irritation, consult a physician.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

In all cases of doubt, or when symptoms persist, seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3. Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media



according to Regulation (EC) No 1907/2006

DEKASEAL 8936 BLACK

Revision date: 04.03.2021 Product code: 1145 Page 3 of 11

Suitable extinguishing media

Carbon dioxide (CO2) Water spray jet alcohol resistant foam

Unsuitable extinguishing media

No further relevant information available.

5.2. Special hazards arising from the substance or mixture

No further relevant information available.

5.3. Advice for firefighters

Use suitable breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

Avoid contact with skin, eyes and clothes.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Provide adequate ventilation.

Clear contaminated areas thoroughly.

Do not rinse down with water.

Other information

No information available.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only in well-ventilated areas.

Advice on protection against fire and explosion

No special measures are necessary.

Further information on handling

No further relevant information available.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

No special measures are necessary.



according to Regulation (EC) No 1907/2006

DEKASEAL 8936 BLACK

Revision date: 04.03.2021 Product code: 1145 Page 4 of 11

Hints on joint storage

Not required.

Further information on storage conditions

No further relevant information available.

7.3. Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
7727-43-7	Barium sulphate, inhalable dust	-	10		TWA (8 h) WEI	
1317-65-3	Calcium carbonate, respirable	-	4		TWA (8 h)	WEL
1333-86-4	Carbon black	-	3.5		TWA (8 h)	WEL
		-	7		STEL (15 min)	WEL
546-93-0	Magnesite, respirable dust	-	4		TWA (8 h)	WEL
14807-96-6	Talc respirable dust	-	1		TWA (8 h)	WEL



according to Regulation (EC) No 1907/2006

DEKASEAL 8936 BLACK

Revision date: 04.03.2021 Product code: 1145 Page 5 of 11

DNEL/DMEL values

CAS No	Substance			
DNEL type	Gastano	Exposure route	Effect	Value
7727-43-7	Barium sulfate			
Worker DNEL	., long-term	inhalation	systemic	10 mg/m³
Worker DNEL	., long-term	inhalation	local	10 mg/m³
Consumer DN	NEL, long-term	inhalation	systemic	10 mg/m³
Consumer DN	NEL, long-term	oral	systemic	13000 mg/kg bw/day
	Hydrocarbons, C7, n-alkanes, isoalkanes, cy	clics		
Consumer DN	NEL, long-term	oral	systemic	149 mg/kg bw/day
Worker DNEL	., long-term	dermal	systemic	300 mg/kg bw/day
Consumer DN	NEL, long-term	dermal	systemic	149 mg/kg bw/day
Worker DNEL	., long-term	inhalation	systemic	2085 mg/m ³
Consumer DN	NEL, long-term	inhalation	systemic	477 mg/m³
	Hydrocarbons, C6, isoalkanes, <5% n-hexan	e		
Worker DNEL, long-term		inhalation	systemic	5306 mg/m ³
Worker DNEL, long-term		dermal	systemic	13964 mg/kg bw/day
Consumer DN	NEL, long-term	inhalation	systemic	1131 mg/m³
Consumer DNEL, long-term		dermal	systemic	1377 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	1301 mg/kg bw/day
546-93-0	Magnesium carbonate			
Consumer DN	NEL, long-term	oral	systemic	7,23 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	7,23 mg/kg bw/day
1333-86-4	Carbon Black			
Worker DNEL	., long-term	inhalation	systemic	2 mg/m³
Worker DNEL, long-term		inhalation	local	2 mg/m³

PNEC values

CAS No	Substance		
Environmental compartment		Value	
7727-43-7	Barium sulfate		
Freshwater		0,115 mg/l	
Freshwater sediment		600,4 mg/kg	
Micro-organisms in sewage treatment plants (STP) 62,2 mg		62,2 mg/l	
Soil 207,7 m		207,7 mg/kg	
1333-86-4	Carbon Black		
Freshwater 5 mg/l		5 mg/l	
Marine water 5 mg/l		5 mg/l	

8.2. Exposure controls



according to Regulation (EC) No 1907/2006

DEKASEAL 8936 BLACK

Revision date: 04.03.2021 Product code: 1145 Page 6 of 11





Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn

Protective and hygiene measures

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Eye/face protection

Recommended eye protection articles:

Eye glasses with side protection (DIN EN 166)

Hand protection

Tested protective gloves must be worn (EN ISO 374):

FKM (fluoro rubber), Breakthrough time (maximum wearing time): 480 min.

NBR (Nitrile rubber), Breakthrough time (maximum wearing time): 480 min.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.

Protect skin by using skin protective cream.

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

Work in well-ventilated zones or use proper respiratory protection.

gas filtering equipment (EN 141)., Filter material/medium: A

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Paste Colour: black

Odour: characteristic
Odour threshold: not determined

Test method

pH-Value: not applicable

Changes in the physical state

Melting point: not determined

Boiling point or initial boiling point and 66-98 °C

boiling range:

Flash point: > 70 °C
Sustaining combustion: No data available

Flammability

Solid/liquid: not determined
Gas: not determined



according to Regulation (EC) No 1907/2006

DEKASEAL 8936 BLACK

Revision date: 04.03.2021 Product code: 1145 Page 7 of 11

Explosive properties

not explosive.

Lower explosion limits:0,6 vol. %Upper explosion limits:7,4 vol. %Auto-ignition temperature:> 200 °CDecomposition temperature:not determinedVapour pressure:not applicable

Density (at 20 °C): 1,3 g/cm³ DIN 51757

Water solubility: Immiscible
Partition coefficient n-octanol/water: not determined
Viscosity / dynamic: 5000 mPa·s

(at 20 °C)

Viscosity / kinematic: not applicable
Solvent content: 15,2 %

9.2. Other information

Solid content: 84,6 %

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No further relevant information available.

10.2. Chemical stability

No hazardous reaction when handled and stored according to provisions.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

No further relevant information available.

10.5. Incompatible materials

No further relevant information available.

10.6. Hazardous decomposition products

Carbon monoxide

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.



according to Regulation (EC) No 1907/2006

DEKASEAL 8936 BLACK

Revision date: 04.03.2021 Product code: 1145 Page 8 of 11

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 >2600 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 >193 mg/l	Rat		

Irritation and corrosivity

Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.2. Persistence and degradability

No further relevant information available.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics			
	OECD 301F	> 60%	28	
	Readily biodegradable (according to OECD criteria).			
	Hydrocarbons, C6, isoalkanes, <5% n-hexane			
OECD 301F > 60% 28				
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

No further relevant information available.

12.4. Mobility in soil

No further relevant information available.

12.5. Results of PBT and vPvB assessment

not applicable

12.6. Endocrine disrupting properties

No further relevant information available.

12.7. Other adverse effects

No further relevant information available.

SECTION 13: Disposal considerations



according to Regulation (EC) No 1907/2006

DEKASEAL 8936 BLACK

Revision date: 04.03.2021 Product code: 1145 Page 9 of 11

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation. Do not mix with other wastes.

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products);

waste adhesives and sealants containing organic solvents or other hazardous substances;

hazardous waste

List of Wastes Code - contaminated packaging

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products);

waste adhesives and sealants containing organic solvents or other hazardous substances;

hazardous waste

Contaminated packaging

Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.Marine pollutant:no

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Maritime transport in bulk according to IMO instruments

No dangerous good in sense of this transport regulation.

Other applicable information



according to Regulation (EC) No 1907/2006

DEKASEAL 8936 BLACK

Revision date: 04.03.2021 Product code: 1145 Page 10 of 11

Tansport classification ADR/IMGD is based on packaging >30ltr(IMDG), <450ltr(ADR). For other packaging until different classification can apply.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2004/42/EC (VOC): 15,22 % 197,9 g/l

Additional information

Observe in addition any national regulations!

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

Additional information

This mixture contains the following substances of very high concern (SVHC) which are included in the

Candidate List according to Article 59 of REACH: none

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.

H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.





according to Regulation (EC) No 1907/2006

DEKASEAL 8936 BLACK

Revision date: 04.03.2021 Product code: 1145 Page 11 of 11

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)